



A	-	C	-	M3	-	1	-	X	
A	-	S	-	M3	-	1	-	ZU	
A	-	4	-	M3	-	1	-	X	
↓	产品	↓	材料	↓	螺纹	↓	尾缀	↓	表面
↓	类型	↓	代码	↓	代码	↓	代码	↓	处理
↓		↓		↓		↓		↓	类型

所有尺寸：毫米

公制螺纹	螺纹规格	非自锁			自锁			螺纹代码	尾缀代码	A Max.	最小板厚	板开口尺寸 +0.08	C Max.	D Max.	E ± 0.38	T1 Max.	T2 Max.	孔中心到板边缘的最小距离
		螺母材料			螺母材料													
		碳钢	300系列不锈钢	400系列不锈钢	碳钢	300系列不锈钢	400系列不锈钢											
M3x0.5	AS	AC	A4	LAS	LAC	LA4	M3	1	0.97	1.0	7.37	7.35	7.37	9.14	3.31	4.83	7.62	
								2 <sup>(1)</sup>	1.38	1.4								
M4x0.7	AS	AC	A4	LAS	LAC	LA4	M4	1	0.97	1.0	9.35	9.33	9.28	11.18	3.31	5.34	8.64	
								2 <sup>(1)</sup>	1.38	1.4								
M5x0.8	AS	AC	A4	LAS	LAC	LA4	M5	1	0.97	1.0	10.31	10.29	10.29	11.94	4.32	6.86	9.14	
								2 <sup>(1)</sup>	1.38	1.4								
M6x1.0	AS	AC	-	LAS	LAC	-	M6	2	1.38	1.4	13.08	13.06	12.96	15.24	5.34	7.88	10.67	

所有尺寸：英寸

英制螺纹	螺纹规格	非自锁			自锁			螺纹代码	尾缀代码	A Max.	最小板厚	板开口尺寸 +.003/- .000	C Max.	D Max.	E ± .015	T1 Max.	T2 Max.	孔中心到板边缘的最小距离
		螺母材料			螺母材料													
		碳钢	300系列不锈钢	400系列不锈钢	碳钢	300系列不锈钢	400系列不锈钢											
.112-40 (#4-40)	AS	AC	A4	LAS	LAC	LA4	440	1	.038	.038	.290	.289	.290	.360	.130	.190	.30	
								2 <sup>(1)</sup>	.054	.054								
.138-32 (#6-32)	AS	AC	A4	LAS	LAC	LA4	632	1	.038	.038	.328	.327	.335	.390	.130	.200	.32	
								2 <sup>(1)</sup>	.054	.054								
.164-32 (#8-32)	AS	AC	A4	LAS	LAC	LA4	832	1	.038	.038	.368	.367	.365	.440	.130	.210	.34	
								2 <sup>(1)</sup>	.054	.054								
.190-24 (#10-24)	AS	AC	-	LAS	LAC	-	024	1	.038	.038	.406	.405	.405	.470	.170	.270	.36	
								2	.054	.054								
.190-32 (#10-32)	AS	AC	A4	LAS	LAC	LA4	032	1	.038	.038	.406	.405	.405	.470	.170	.270	.36	
								2 <sup>(1)</sup>	.054	.054								
.250-20 (1/4-20)	AS	AC	-	LAS	LAC	-	0420	2	.054	.054	.515	.514	.510	.600	.210	.310	.42	
.250-28 (1/4-28)	AS	AC	-	LAS	LAC	-	0428	2	.054	.054	.515	.514	.510	.600	.210	.310	.42	

(1) 这个尾缀码对应的产品不适用于A4和LA4系列