



所有尺寸：毫米

公制螺纹	螺纹规格	规格型号			螺纹代码	尾缀代码	A Max.	最小板厚	板开口尺寸 +0.08	C Max.	D Max.	E Nom.	T ±0.25	孔中心到板边缘的最小距离
		螺母材料												
		碳钢	不锈钢	铝合金										
M2.5x0.45	LK	LKS	LKA	M2.5	1	0.97	1.0	4.37	4.35	4.45	6.35	3.43	3.9	
					2	1.38	1.4							
M3x0.5	LK	LKS	LKA	M3	1	0.97	1.0	4.75	4.73	4.85	6.35	3.43	4.0	
					2	1.38	1.4							
M4x0.7	LK	LKS	LKA	M4	1	0.97	1.0	6.76	6.73	6.2	8.73	4.45	5.2	
					2	1.38	1.4							
M5x0.8	LK	LKS	LKA	M5	1	0.97	1.0	7.92	7.9	7.4	9.53	5.21	5.6	
					2	1.38	1.4							

所有尺寸：英寸

英制螺纹	螺纹规格	规格型号			螺纹代码	尾缀代码	A Max.	最小板厚	板开口尺寸 +.003/ -.0	C Max.	D Max.	E Nom.	T ±.010	孔中心到板边缘的最小距离
		螺母材料												
		碳钢	不锈钢	铝合金										
.086-56 (#2-56)	LK	LKS	LKA	256	1	.038	.040	.172	.171	.165	.250	.135	.156	
					2	.054	.056							
.112-40 (#4-40)	LK	LKS	LKA	440	1	.038	.040	.187	.186	.185	.250	.135	.156	
					2	.054	.056							
.138-32 (#6-32)	LK	LKS	LKA	632	1	.038	.040	.219	.218	.220	.312	.145	.187	
					2	.054	.056							
.164-32 (#8-32)	LK	LKS	LKA	832	1	.038	.040	.266	0.27	.250	.343	.175	.203	
					2	.054	.056							
.190-32 (#10-32)	LK	LKS	LKA	032	1	.038	.040	.312	.311	.285	.375	.205	.218	
					2	.054	.056							